

<https://doi.org/10.56770/jcp202610110>

A COMPARATIVE REVIEW ON TECHNICAL ASPECTS ON MOLECULAR DOCKING TECHNIQUES

Muhammad Naeem Aamir^{1*} , Muhammad Munawar Hayat²

¹Department of Pharmaceutics, The Islamia University of Bahawalpur, Punjab, Pakistan.

²Director, Pakistan Drug Testing & Research Centre, Sundar Industrial Estate Lahore, Pakistan.

Submitted: February 27, 2026; Revised: April 9, 2026; Accepted: June 2, 2025; Published: June 30, 2026

ABSTRACT

Because it makes it easier to comprehend how tiny compounds interact with target proteins, molecular docking is an essential computational technique in drug discovery and development. The purpose of this study is to provide light on the development of molecular docking methods, their present uses, and their promise for the future. We investigate the approaches employed in molecular docking investigations by a comprehensive survey of the literature and analysis of current developments. We go over the evolution from conventional rigid docking techniques to more sophisticated flexible and ensemble docking approaches, emphasizing the advantages and disadvantages of each. Significant progress has been made in molecular docking over the last ten years, including advances in scoring functions, algorithms, and computational resource accessibility. There are still issues, though, especially when it comes to precisely estimating ligand binding affinities and taking protein flexibility into consideration. Furthermore, interesting prospects for more accurate modeling of ligand-protein interactions are presented by the development of hybrid techniques that integrate docking with molecular dynamics simulations. To sum up, molecular docking continues to be a fundamental component of structure-based drug design, supporting lead compound discovery and optimization. Despite these developments, docking procedures still need to be improved in order to overcome current constraints and fully utilize computational techniques' promise to accelerate the drug discovery process.

Keywords: Molecular docking, Types, Limitations, Applications.

*Corresponding Author. E-mail: naeem.aamir@iub.edu.pk

INTRODUCTION

Because it predicts the orientation of tiny molecules when they bind to target proteins, molecular docking is an essential computational tool in drug discovery and design. By improving our knowledge of how chemicals and proteins interact, this technique makes it easier to create novel therapeutic medicines. Since its inception in the 1980s, molecular docking has become much more accurate and efficient due to continuous improvements in algorithms and processing power. Today, molecular docking serves as a vital tool in pharmaceutical research, helping to find prospective drug candidates and enhance their binding interactions. An overview of the significance and development of molecular docking in drug discovery is provided in this study [1-3].

In order to find possible binding sites and maximize the medication's binding affinity and specificity, researchers can model and examine the

interactions between drug candidates and target proteins. Molecular docking is a useful technique for evaluating vast chemical libraries and forecasting their potential as therapeutic candidates. Manual drug studies, on the other hand, use a more conventional method in which scientists test and examine drug candidates' interactions with target proteins through experimentation. In order to comprehend binding mechanisms and improve the drug's efficacy, this process frequently uses methods like crystallography and biochemical testing. Manual drug studies produce more precise and in-depth information regarding drug-target interactions, while molecular docking offers a quicker and more economical way to screen and analyze possible drug candidates.

Both strategies have advantages and disadvantages, and they are frequently combined to enhance one another during the drug discovery process. The

Journal of Contemporary Pharmacy is published by AMMANIF. The authors retain the copyright without restriction. This article is an open access article published under the terms and conditions of [Creative Commons Attribution 4.0 International License](https://creativecommons.org/licenses/by/4.0/).



decision between molecular docking and manual drug studies ultimately comes down to the particular study objectives, the resources at hand, and the intricacy of the drug-target interactions under investigation.

Since its inception in the late 20th century, molecular docking in drug development has advanced significantly. Predicting how tiny compounds bind to target proteins was made possible by the development of the first molecular docking algorithms in the 1980s. In order to help in drug design, these early attempts sought to comprehend the structural and energetic elements of molecular interactions [4-7].

Predicting ligand-protein interactions became more accurate and efficient in the 1990s due to improvements in processing capacity and algorithm development. To better mimic the binding process and find possible medication candidates, a number of scoring systems and search algorithms were created during this time. Pharmaceutical corporations and academic organizations began integrating molecular docking into their drug development pipelines by the early 2000s, as it was widely acknowledged as an essential tool in drug discovery.

The purpose of this paper is to shed light on the development of molecular docking methods, their present uses, and possible future paths. We offer insights into the approaches employed in molecular docking investigations by performing a thorough literature analysis and examining current developments [8, 9].

The integration of molecular docking with other computational and experimental methods has significantly enhanced its utility in rational drug

design and optimization. Today, molecular docking plays a crucial role in drug discovery, allowing researchers to screen large compound libraries, predict binding affinities, and optimize drug candidates with increased precision. The field is continually evolving, with ongoing research focused on improving accuracy, speed, and applicability to various biological targets. Several types of molecular docking methods are commonly employed in drug discovery and computational biology [10-12].

RIGID DOCKING

In this approach, both the ligand (a small molecule) and the receptor (the target protein) are kept fixed during the docking process. While this method is faster, it does not account for potential conformational changes in the protein that may occur upon ligand binding. In molecular modeling, rigid docking—also called rigid-body docking or geometric docking—is a computer method that predicts the atomic-level binding mechanism and affinity between a ligand and a receptor, usually a protein. It ignores any conformational changes that may occur upon binding and assumes that both the ligand and the receptor maintain rigid structures throughout the docking process [13-16]. The geometric complementarity between the ligand and receptor structures is essential to rigid docking. Predicting the ligand's most energetically advantageous conformation inside the receptor's binding region is the aim. This entails navigating the ligand's vast conformational space to find the position that minimizes steric conflicts and optimizes advantageous interactions, such as hydrophobic contacts, van der Waals forces, and hydrogen bonding.




Figure 1: Salient types of docking.

Methods of Rigid Docking

Various computational algorithms and software tools have been developed for rigid docking. These methods typically follow these steps:

a) Preparation: Water molecules are eliminated, hydrogen atoms are added, partial charges are assigned, and the geometry is optimized as needed to create the receptor and ligand structures.

b) Search Algorithm: To explore the ligand's conformational space and identify the ideal binding pose, docking algorithms employ a variety of search techniques. Geometric hashing, Monte Carlo techniques, evolutionary algorithms, and methodical grid-based searches are common tactics.

c) Scoring Function:

Following the creation of potential ligand poses, a scoring mechanism assesses and prioritizes these poses according to their anticipated binding affinities. Geometric complementarity, electrostatic interactions, van der Waals forces, and desolvation energy are commonly taken into account by scoring functions.

d) Post-Processing and Analysis: Lastly, post-processing methods examine intermolecular interactions and improve the predicted binding postures. Researchers can analyze the docked complexes and pinpoint important binding residues and interactions by using visualization tools [11-19].

Applications and Limitations of Rigid Docking

It is widely used in computer-aided drug design (CADD) to find possible therapeutic candidates that bind to target proteins with high affinity and specificity by screening vast libraries of chemical compounds. Protein inhibitors and modulators can be designed with the use of rigid docking, which can also be used to predict the binding modes between two protein molecules. Researchers can support rational drug design and enzyme engineering by elucidating enzyme-substrate interactions and proposing mechanisms of enzyme catalysis by the docking of small molecules into the active sites of enzymes. A key component of virtual screening workflows is rigid docking, which involves computationally screening vast databases of chemical compounds to rank those for experimental testing according to their anticipated binding affinities to target proteins.

Rigid docking assumes that both the ligand and receptor maintain rigid structures, overlooking any conformational changes that may occur upon binding. This limitation can lead to inaccuracies in predicting binding affinities and modes, particularly for flexible ligands or receptors. The reliability of rigid docking predictions relies heavily on the scoring function used to evaluate binding poses. However, many current scoring functions fail to capture all relevant molecular

interactions accurately, which can result in false positives or false negatives. When performing high-throughput virtual screening or investigating vast conformational regions, docking simulations can be computationally demanding. The size of the systems that may be examined is restricted by this complexity, which also calls for effective methods and parallel computing resources. Rigid docking usually disregards the influence of solvent molecules on ligand-receptor interactions and assumes a dry binding site. However, binding affinity and selectivity can be greatly impacted by solvent effects, necessitating more advanced modeling techniques [20-22].

FLEXIBLE DOCKING

During the docking process, flexible docking allows for flexibility in the ligand, receptor, or both. This method can produce more precise predictions of binding modes by accounting for conformational changes. It is a computational method in molecular modeling that predicts the binding mechanism and affinity between a ligand and a receptor while taking into account the flexibility of both structures. It is also known as flexible ligand docking or induced-fit docking. Flexible docking acknowledges that both the ligand and the receptor may undergo conformational changes upon contact, in contrast to rigid docking, which presumes that both remain in fixed conformations during interaction. Reflecting the dynamic character of biomolecular structures and the induced-fit phenomenon in ligand-receptor interactions is the fundamental idea behind flexible docking. In order to maximize their interactions and create a stable bound complex, both the ligand and the receptor may undergo conformational changes as they engage. In order to provide a more accurate depiction of the binding process, flexible docking attempts to anticipate both the binding pose and the accompanying conformational changes of the ligand and receptor.

Methods of Flexible Docking

Conformational Sampling: In contrast to rigid docking, flexible docking explores the conformational space and finds energetically advantageous binding poses by sampling several ligand and receptor conformations. Methods like normal mode analysis, systematic conformational search techniques, and molecular dynamics simulations are frequently used.

Flexible docking methods typically involve several key steps: 1. Flexible docking algorithms anticipate the ideal ligand binding pose within the flexible binding site of the receptor by combining conformational sampling with conventional docking search techniques. These algorithms direct the search toward the most advantageous binding poses by using scoring functions to assess each ligand conformation's compatibility with the

receptor. 2. In flexible docking, scoring functions are crucial for ranking the anticipated binding poses and evaluating the energetics of ligand-receptor interactions. Geometric complementarity, electrostatic interactions, van der Waals forces, solvation effects, and conformational strain are some of the variables that these functions usually take into account. 3. In order to explicitly account for conformational changes in the receptor during ligand binding, certain flexible docking systems use induced-fit modeling techniques. To precisely represent induced-fit effects, this may need loop refinement, flexible side-chain modeling, or even entire protein backbone flexibility. 4. Following the creation of potential ligand poses, post-processing methods improve the forecasts and examine interactions between molecules. Researchers can look at docked complexes and find important binding residues and conformational changes using visualization tools [23-27].

Applications and Limitations of Flexible Docking

It is often utilized in lead optimization and virtual screening to forecast the selectivity and binding affinity of small molecule ligands to target proteins. Flexible docking can find ligands that rigid docking techniques might miss by accounting for receptor flexibility, leading to more precise predictions of binding affinity and efficacy. Flexible docking sheds light on the molecular mechanisms underlying interactions between proteins and ligands, particularly the induced-fit effects that follow ligand binding. Flexible docking clarifies the structural underpinnings of ligand recognition and binding selectivity by simulating conformational changes in the receptor. Flexible docking is used in enzymology to forecast the mechanisms and patterns of binding of enzyme inhibitors. Flexible docking makes it easier to create powerful and specific enzyme inhibitors with therapeutic potential by accounting for the flexibility of both ligands and receptors. In virtual screening operations, where large databases of chemical compounds are computationally processed to find possible drug candidates, flexible docking is essential. Flexible docking improves hit identification and lead optimization efforts by adding receptor flexibility, which increases the accuracy of virtual screening predictions.

Flexible docking simulations can be resource-intensive, particularly when modeling large biomolecular systems or conducting extensive conformational sampling. The high computational demands limit the scalability of flexible docking techniques and necessitate the use of efficient algorithms and parallel computing resources. The scoring algorithms used to evaluate ligand-receptor interactions and rank binding poses have a significant impact on the accuracy of flexible

docking predictions. Predicted binding affinities and poses may be inaccurate if current scoring systems fail to completely capture all pertinent molecular interactions. Because it affects the range of ligand and receptor conformations investigated throughout the docking process, conformational sampling is essential to flexible docking. However, thorough sampling can be challenging, particularly for large biomolecular systems with complex energy landscapes. Accurately modeling receptor flexibility remains a significant challenge in flexible docking. While some methods, like induced-fit docking, allow for explicit modeling of receptor flexibility, others depend on simplified representations or predefined conformational ensembles [28-34].

INDUCED FIT DOCKING

Both rigid and flexible docking techniques are incorporated into induced fit docking. In order to accommodate induced fit effects, the complex is refined by adjusting flexible side chains or backbone motions after initial docking utilizing stiff structures. This computational method is used in molecular modeling to explicitly account for conformational changes in both structures during interaction while predicting the binding mode and affinity between a ligand and a receptor. Induced fit docking acknowledges the dynamic character of biomolecular interactions and the induced-fit phenomenon in ligand-receptor binding, in contrast to rigid docking, which presumes that both the ligand and the receptor stay in fixed conformations throughout the binding process. The fundamental principle of induced fit docking is to capture the dynamic nature of biomolecular interactions, where both the ligand and receptor can undergo conformational changes to optimize their interaction and form a stable bound complex. Initially, the ligand and receptor structures undergo independent conformational sampling to explore their respective conformational spaces. This step involves generating multiple conformations of both the ligand and receptor using techniques such as molecular dynamics simulations, normal mode analysis, or systematic conformational search algorithms. The ligand is placed inside the binding site of the receptor during the docking process, which enables both entities to simultaneously modify their conformations. Because the receptor is regarded as flexible, it can adjust its conformation to accommodate the binding ligand. This adaptability makes it easier for the receptor to adopt conformations that improve interactions with the ligand and produce a stable bound complex.

Methods of Induced-Fit Docking

It involves steps: 1. Conformational Sampling: Conformational sampling is used to generate an ensemble of conformations that represent the flexibility of both the ligand and the receptor. This

could entail systematic conformational search techniques, normal mode analysis, or molecular dynamics simulations. 2. To determine the ideal binding position of the ligand inside the flexible binding site of the receptor, induced fit docking algorithms combine conformational sampling with conventional docking search techniques. In order to direct the search toward the most advantageous binding poses, these algorithms usually use scoring functions to assess each ligand conformation's compatibility with the receptor conformations. 3. In induced fit docking, scoring functions rank anticipated binding poses according to geometric complementarity, electrostatic interactions, van der Waals forces, solvation effects, and conformational strain in order to assess the energetics of ligand-receptor interactions. From the ensemble of docked complexes, these functions are essential for choosing the most stable and physiologically relevant binding poses. 4. Post-processing methods improve predictions and examine intermolecular interactions following the generation of candidate ligand poses. Researchers can study docked complexes and find important binding residues, conformational changes, and induced-fit effects by using visualization techniques [35-39].

Applications and Limitations of Induced Fit Docking

In lead optimization, induced fit docking is used to forecast the selectivity and binding affinity of small molecule ligands for target proteins. This method finds ligands that rigid docking techniques might miss by explicitly taking receptor flexibility into account, resulting in more precise estimates of binding affinity and efficacy. To screen fragment libraries and forecast how small molecular fragments will attach to target proteins, fragment-based drug design employs induced fit docking. This approach finds fragment hits that can be refined into high-affinity lead compounds by utilizing receptor flexibility. In virtual screening procedures, where massive chemical compound databases are computationally examined to identify possible drug candidates, induced fit docking is essential. Induced fit docking improves prediction accuracy, hit identification, and optimization efforts by taking receptor flexibility into account. The molecular mechanisms of ligand-receptor interactions, in particular the induced-fit effects that arise upon ligand binding, can be better understood by the use of induced fit docking. It makes clear the structural underpinnings of ligand recognition and binding selectivity by simulating conformational changes in the receptor.

Simulations can be computationally demanding, particularly when modeling large biomolecular systems or conducting extensive conformational sampling. These high costs can limit the scalability of induced fit docking approaches and necessitate

the use of efficient algorithms and parallel computing resources. The predictions made by induced fit docking largely depend on the accuracy of the scoring functions that evaluate ligand-receptor interactions and rank binding poses. Existing scoring functions may not fully capture all relevant molecular interactions, potentially leading to inaccuracies in predicted binding affinities and poses. The breadth of conformational sampling is vital in induced fit docking, influencing the range of ligand and receptor conformations explored during the process. However, exhaustive sampling can be challenging, especially for large biomolecular systems with complex energy landscapes. Accurately modeling receptor flexibility is a significant challenge in induced fit docking. While some methods allow for explicit flexibility modeling, others depend on simplified representations or predefined conformational ensembles [40-44].

LIGAND-BASED DOCKING

In ligand-based docking, the ligand molecule's characteristics are prioritized over the receptor's structure. When the receptor structure is unknown or challenging to obtain, this method is especially helpful. This computational method, also known as ligand-centric docking or structure-based pharmacophore modeling, forecasts a ligand's binding mechanism and affinity to a target receptor or enzyme without specifically taking the receptor's structure into account. Ligand-based docking only uses data from the ligand itself, such as its structure, chemical characteristics, and interactions with the target, as opposed to receptor-based docking techniques, which necessitate knowledge of the receptor structure. By comparing a ligand's resemblance to known ligands with empirically verified activities, the basic idea behind ligand-based docking is to deduce the binding mechanism and affinity of a ligand to a target receptor. These techniques use pharmacophore mapping and molecular similarity to pinpoint crucial structural elements and functional groups necessary for ligand binding and biological activity. Ligand-based docking predicts the binding affinity and selectivity of novel ligands for the target receptor by examining the molecular characteristics and spatial configurations of ligands.

Methods of Ligand-Based Docking

Its steps are: 1. Ligand Selection and Dataset Preparation: Choosing a dataset of structurally varied ligands with proven actions against the target receptor is the first step in ligand-based docking. When creating pharmacophore models and doing similarity searches, these ligands are used as reference molecules. Typically, the dataset is selected from virtual screening libraries or experimental databases. 2. Pharmacophore Generation: The spatial arrangement of important

functional groups and molecular characteristics that support ligand binding and biological activity is the basis for the creation of pharmacophore models. Aromatic rings, hydrophobic areas, hydrogen bond donors, and acceptors are common pharmacophore characteristics. Pharmacophore creation algorithms define the spatial interactions between active ligands and find common features. 3 Once the pharmacophore model has been created, it is used to look for molecules with comparable chemical characteristics and spatial configurations in virtual compound libraries. Candidate ligands that match the pharmacophore model are found using ligand-based similarity search techniques such as shape-based similarity, 3D pharmacophore overlays, and 2D fingerprints. Virtual screening predicts these potential ligands' binding affinity to the target receptor and ranks them according to how similar they are to known active molecules. 4. To determine their binding affinity and selectivity, candidate ligands found through virtual screening are further assessed using scoring functions. These scoring functions consider factors such as pharmacophore fit, molecular properties, and energy calculations to prioritize ligands for experimental testing. Validating ligand-based docking models is crucial to assess their predictive accuracy and reliability, using benchmark datasets and experimental assays [45-47].

Applications and Limitations of Ligand-Based Docking

This approach helps identify lead compounds with potential activity against specific receptors or enzymes. By searching virtual compound libraries for molecules that share chemical features and biological activities with known ligands, ligand-based docking facilitates the discovery of novel leads for further experimental testing. Ligand-based docking plays a crucial role in virtual screening workflows, where large databases of chemical compounds are computationally screened to prioritize candidates for experimental testing. By utilizing molecular similarity and pharmacophore mapping, this method allows for the rapid identification of potential drug candidates with desirable pharmacological profiles. In the lead optimization phase, ligand-based docking guides the design of new compounds with enhanced binding affinity and selectivity. By analyzing the structure-activity relationships of known ligands and pinpointing key pharmacophore features, it aids in optimizing chemical scaffolds and functional groups for improved ligand potency and drug-like properties. Ligand-based docking supports bioisosteric replacement by identifying structurally similar compounds that can replace key functional groups or chemical moieties in known ligands. By exploring chemical space and finding analogs with comparable pharmacological profiles,

this technique assists in designing novel ligands that offer improved efficacy and reduced off-target effects.

The availability of reference ligands with proven activity against the target receptor is a prerequisite for this approach. The predictions generated by ligand-based docking may be erroneous if appropriate reference ligands are absent or if the dataset is skewed or deficient. Ligand-based docking is appropriate for targets with unknown or challenging-to-obtain structures because it does not require knowledge of the target receptor's structure. However, the lack of structural knowledge may limit the predictions' interpretability and accuracy, particularly for targets with allosteric modulation or complex binding sites. The scoring algorithms used to rank potential ligands have a significant impact on the accuracy of ligand-based docking predictions. The intricacy of ligand-receptor interactions may not be well captured by current scoring systems, which could lead to false positives or negatives in virtual screening results. This method ignores conformational changes or induced-fit effects that might occur upon ligand binding by assuming that the target receptor retains a rigid shape throughout ligand binding. Prediction accuracy may be impacted by this restriction, especially for targets with dynamic or flexible binding sites [48-53].

PROTEIN-PROTEIN DOCKING

Understanding protein complexes and signaling pathways depends on the ability to predict interactions between two protein molecules through protein-protein docking. Protein molecules' three-dimensional structure and mode of interaction are predicted using this computational method in molecular modeling. It is essential for understanding the mechanisms of protein-protein interactions (PPIs), which are essential to many biological processes, including gene regulation, immunological response, and signal transduction. The concepts, procedures, uses, and constraints of protein-protein docking in molecular modeling will all be covered in this essay. The principle behind protein-protein docking is to predict the binding mode and affinity between two protein molecules by exploring their conformational space and identifying energetically favorable binding configurations. Protein-protein interactions are mediated by complementary surfaces on the proteins, where specific amino acid residues form intermolecular contacts, including hydrogen bonds, hydrophobic interactions, and electrostatic interactions. The goal of protein-protein docking is to model these interactions and predict the spatial arrangement of the interacting proteins in the bound complex.

Methods of Protein-Protein Docking

Protein-protein docking methods generally involve

the following steps: 1. The initial step in protein-protein docking is preparing the protein structures. This includes removing water molecules, adding missing atoms, assigning partial charges, and optimizing hydrogen bond networks. Protein structures are often derived from experimental techniques such as X-ray crystallography or NMR spectroscopy. 2. To investigate the conformational space of the interacting proteins and find possible binding poses, protein-protein docking systems use a variety of search techniques. Geometric hashing, Monte Carlo techniques, genetic algorithms, and stochastic optimization approaches are examples of common search algorithms. Based on geometric complementarity and intermolecular interactions, these algorithms assess the compatibility of various protein orientations and conformations. 3. Following the generation of candidate binding poses, a scoring function assesses and ranks these poses according to their anticipated stability and binding affinity. Shape complementarity, electrostatic interactions, van der Waals forces, desolvation energy, and interface area are all commonly taken into account by scoring functions. Differentiating between non-specific interactions and native-like binding postures is the goal of the scoring function. 4. Lastly, post-processing methods examine intermolecular interactions and improve the anticipated binding postures. Researchers can analyze the docked complexes and pinpoint important binding residues and interaction surfaces by using visualization tools. To further optimize the docked structures and investigate their dynamic behavior, energy minimization methods or molecular dynamics simulations may be used [54, 55].

Applications and Limitations of Protein-Protein Docking

To ascertain the three-dimensional architectures of protein complexes and comprehend the molecular underpinnings of protein-protein interactions, protein-protein docking is utilized. This method sheds light on the mechanisms of complex formation and activity by forecasting the binding modalities and interface residues of interacting proteins. Protein-protein docking is essential for finding possible inhibitors or modulators of protein-protein interactions in structure-based drug design. It makes it easier to rationally design tiny compounds or peptides that disrupt abnormal protein complexes and stop the progression of disease by focusing on particular interfaces involved in disease pathways. By anticipating the interaction partners and binding modalities of proteins, this method helps annotate their functions. Protein-protein docking provides important insights into the function and regulation of proteins by identifying complexes engaged in cellular processes and signaling cascades through the

analysis of the protein-protein interaction network. To find possible inhibitors of protein-protein interactions, libraries of small compounds or peptides are computationally screened using protein-protein docking, a crucial component of virtual screening procedures. Candidates for experimental testing are ranked according to expected binding affinity and interaction specificity by docking these chemicals into the binding sites of target proteins.

Finding the ideal binding position of interacting proteins requires navigating a large conformational space. However, comprehensive conformational sampling can be computationally challenging, especially for large protein complexes containing dynamic or flexible areas. Sampling restrictions may make it impossible to determine the native-like complex structure and explore all pertinent binding postures. The scoring function used to assess binding poses has a significant impact on how reliable docking predictions are. The complexity of protein-protein interactions may not be fully captured by current scoring systems, which could lead to false positives or negatives in complex structure identification as well as inaccurate binding affinity estimates. Protein-protein docking frequently ignores conformational changes or induced-fit effects that might arise during complex formation by assuming that both interacting proteins maintain rigid conformations throughout binding. Protein flexibility is still a major problem, especially for big complexes with allosteric regulation or flexible binding sites. Although protein-protein docking offers insightful information on the structure and modalities of interaction of protein complexes, experimental validation is essential to validate predicted binding poses and evaluate the biological significance of interactions found. To verify docking predictions and clarify the functional importance of protein-protein interactions, methods like X-ray crystallography, NMR spectroscopy, or biochemical experiments are required [56-60].

BLIND DOCKING

A technique known as "blind docking" entails binding a ligand to a receptor's whole surface without designating a binding location. This method works especially well for identifying possible interactions and binding locations. This computer method, also known as global docking or blind protein-ligand docking, is used in molecular modeling to predict a ligand's binding mechanism and affinity to a receptor without knowing the receptor's binding location beforehand. Blind docking looks at the entire surface of the receptor to find potential binding sites and discover the best ligand binding configurations, in contrast to typical docking approaches that rely on specific structural information to guide the docking process. The

fundamental idea behind blind docking is to anticipate the binding mechanism and affinity of ligands while searching the whole receptor surface for possible binding sites. This method is perfect for targets with unknown or flexible binding sites because it doesn't require any prior knowledge about the position or structure of the binding site. A grid or mesh of points encompassing the whole receptor surface is sampled by blind docking algorithms, which assess possible binding configurations at each location using scoring functions and intermolecular interactions.

Methods of Blind Docking

Blind docking typically involves the following steps: 1. The full surface of the receptor structure is depicted as a three-dimensional grid or mesh. The resolution of the search space is determined by the grid spacing; smaller spacing permits finer sampling but raises computing expenses. Masking or eliminating portions of the receptor surface that are unlikely to bind ligands, such as solvent-exposed areas or regions with high conformational flexibility, may also be part of this stage. 2. To dock ligands into the receptor grid, a library of ligand conformations is created or chosen. Random sampling, systematic sampling, and fragment-based techniques are examples of ligand sampling techniques. Usually, the ligand conformations are obtained by either sampling from a database of known ligand structures or by investigating the ligand's conformational space. 3. Using a variety of methodologies, including geometric hashing, Monte Carlo methods, evolutionary algorithms, and stochastic optimization techniques, blind docking programs look for possible binding poses of the ligand within the receptor grid. Potential binding poses are assessed using geometric complementarity and intermolecular interactions with the receptor after ligand conformations are arranged either methodically or randomly within the grid. 4. Following the generation of candidate binding poses, these poses are assessed and ranked according to their anticipated binding affinity and stability using a scoring function. Geometric complementarity, electrostatic interactions, van der Waals forces, desolvation energy, and contact area are all taken into account by this function. Differentiating between non-specific interactions and native-like binding poses is the aim. 5. Lastly, post-processing methods examine intermolecular interactions and improve the anticipated binding postures. Researchers can study the docked complexes and find possible binding sites on the receptor surface using visualization techniques. To further optimize the docked structures and investigate their dynamic behavior, energy minimization methods or molecular dynamics simulations may be used [61-63].

Applications and Limitations of Blind Docking

Potential binding sites on target proteins can be found via blind docking, which can also forecast ligand affinities and binding modalities. Blind docking finds new binding sites that might not be seen from homology models or experimental structures by looking at the receptor's whole surface. To find possible drug candidates, blind docking scans chemical compound libraries as a crucial part of virtual screening operations. It makes it easier to find ligands with a variety of chemical scaffolds and binding mechanisms by examining the whole receptor surface. This results in the identification of new lead compounds for additional experimental validation. Blind docking is used in fragment-based drug design to screen libraries of small molecular fragments and anticipate how they will attach to target proteins. Blind docking helps find fragment hits that can be improved into high-affinity lead compounds via linking or growth procedures by examining the entire surface of the receptor. By locating possible ligand binding sites and describing ligand binding behaviors, blind docking helps predict protein function. It aids in the annotation of protein activities and regulation by examining the whole receptor surface and offering insights into the structural underpinnings of protein-ligand interactions.

Blind docking simulations can be computationally taxing, especially when sampling multiple ligand conformations and investigating the full receptor surface. The scalability of blind docking techniques is restricted by these high computational costs, which call for the adoption of effective algorithms and parallel computer resources. Blind docking may have sampling problems, particularly in areas of the receptor surface that are solvent-exposed or show considerable conformational flexibility. Potential binding poses or locations may be overlooked if subterranean cavities or inaccessible binding sites are not sufficiently sampled. The scoring function used to assess binding poses has a significant impact on the accuracy of blind docking predictions. The intricacy of protein-ligand interactions may not be fully taken into account by current scoring systems, which could lead to false positives or negatives in binding site identification as well as inaccurate estimates of binding affinity. Blind docking frequently ignores conformational changes or induced-fit effects that might happen during ligand binding by assuming the receptor stays rigid. In blind docking, addressing receptor flexibility is a major difficulty, especially for targets with dynamic binding sites [64-66].

CONCLUSION

Molecular docking has significantly evolved from a basic tool to a sophisticated computational technique with broad applications in drug

discovery, structural biology, and molecular modeling. As we reflect on its past achievements and current state, we can also envision future directions and advancements that will shape the field in the coming years. Molecular docking is now a crucial component of computational drug development workflows, supporting lead optimization initiatives and enhancing experimental methods. More precise and effective docking simulations have been made possible by the advancement of sophisticated docking algorithms, machine learning techniques, and high-performance computer resources, enabling researchers to investigate broader chemical spaces and tackle challenging biological problems. Virtual screening, fragment-based drug design, and structure-based optimization are important uses of molecular docking in modern drug development. While fragment-based techniques use docking to screen small molecule fragments and create high-

affinity inhibitors via fragment linking or growth strategies, virtual screening campaigns use docking simulations to find lead compounds with possible action against target proteins. Furthermore, by clarifying methods of ligand recognition, protein dynamics, and allosteric control, it keeps improving our knowledge of protein-ligand interactions and the structural underpinnings of therapeutic action. This offers important information for developing treatments that target receptor modification, enzyme inhibition, and protein-protein interactions.

Author(s) Contribution: data collection, M. A. Naeem; proofreading, M. H. Munawar.

Funding: Nill

Ethical Approval: NA

Conflict of Interest: There is no conflict of interest.

Consent for Publication: All authors approved the manuscript for publication and agreed to be responsible for all aspects of this article.

REFERENCES

1. Norel R, Fischer D, Wolfson HJ, Nussinov R. Molecular surface recognition by a computer vision-based technique. *Protein Eng.* 1994;7(1):39–46. doi: 10.1093/protein/7.1.39.
2. Miller MD, Kearsley SK, Underwood DJ, Sheridan RP. FLOG: a system to select ‘quasi-flexible’ ligands complementary to a receptor of known three-dimensional structure. *J Comput Aided Mol Des.* 1994;8(2):153–174. doi: 10.1007/BF00119865.
3. Burkhard P, Taylor P, Walkinshaw MD. An example of a protein ligand found by database mining: description of the docking method and its verification by a 2.3 Å X-ray structure of a thrombin-ligand complex. *J Mol Biol.* 1998;277(2):449–466. doi: 10.1006/jmbi.1997.1608.
4. Kuntz ID, Leach AR. Conformational analysis of flexible ligands in macromolecular receptor sites. *J. Comput. Chem.* 1992;13:730–748.
5. Ewing TJ, Makino S, Skillman AG, Kuntz ID. DOCK 4.0: search strategies for automated molecular docking of flexible molecule databases. *J Comput Aided Mol Des.* 2001;15(5):411–428. doi: 10.1023/a:1011115820450.
6. Welch W, Ruppert J, Jain AN. Hammerhead: fast, fully automated docking of flexible ligands to protein binding sites. *Chem Biol.* 1996;3(6):449–462. doi: 10.1016/s1074-5521(96)90093-9.
7. Schnecke V, Kuhn LA. Virtual Screening with Solvation and Ligand-Induced Complementarity. *Perspectives in Drug Discovery and Design.* 2000;20:171–190.
8. Zsoldos Z, Reid D, Simon A, Sadjad BS, Johnson AP. eHiTS: an innovative approach to the docking and scoring function problems. *Curr Protein Pept Sci.* 2006;7(5):421–435. doi: 10.2174/138920306778559412.
9. Miranker A, Karplus M. Functionality maps of binding sites: a multiple copy simultaneous search method. *Proteins.* 1991;11(1):29–34. doi: 10.1002/prot.340110104.
10. Eisen MB, Wiley DC, Karplus M, Hubbard RE. HOOK: a program for finding novel molecular architectures that satisfy the chemical and steric requirements of a macromolecule binding site. *Proteins.* 1994;19(3):199–221. doi: 10.1002/prot.340190305.
11. Bohm HJ. LUDI: rule-based automatic design of new substituents for enzyme inhibitor leads. *J Comput Aided Mol Des.* 1992;6(6):593–606. doi: 10.1007/BF00126217.
12. Goodsell DS, Lauble H, Stout CD, Olson AJ. Automated docking in crystallography: analysis of the substrates of aconitase. *Proteins.* 1993;17(1):1–10. doi: 10.1002/prot.340170104.
13. Hart TN, Read RJ. A multiple-start Monte Carlo docking method. *Proteins.* 1992;13(3):206–222. doi: 10.1002/prot.340130304.
14. Goodsell DS, Olson AJ. Automated docking of substrates to proteins by simulated annealing. *Proteins.* 1990;8(3):195–202. doi: 10.1002/prot.340080302.
15. Abagyan R, Totrov M, Kuznetsov D. ICM-A new method for protein modeling and design: Applications to docking and structure prediction from the distorted native conformation. *J. Comput. Chem.* 1994;15:488–506.
16. McMartin C, Bohacek RS. QXP: powerful, rapid computer algorithms for structure-based drug design. *J Comput Aided Mol Des.* 1997;11(4):333–344. doi: 10.1023/a:1007907728892.
17. Muhammed MT, Aki-Yalcin E. Molecular docking: Principles, advances, and its applications in drug
18. discovery. *Lett Drug Des Discov.* 2024;21(3):480–95.
19. Oshiro CM, Kuntz ID, Dixon JS. Flexible ligand docking using a genetic algorithm. *J Comput Aided Mol Des.* 1995;9(2):113–130. doi: 10.1007/BF00124402.
20. Verdonk ML, Cole JC, Hartshorn MJ, Murray CW, Taylor RD. Improved protein-ligand docking using

- GOLD. *Proteins*. 2003;52(4):609–623. doi: 10.1002/prot.10465.
21. Clark KP. Ajay, Flexible ligand docking without parameter adjustment across four ligand- receptor complexes. *J Comput Chem*. 1995;16:1210–1226.
22. Taylor JS, Burnett RM. DARWIN: a program for docking flexible molecules. *Proteins*. 2000;41(2):173–191.
23. Cornell WD, Cieplak P, Bayly CI, Gould IR, Merz KM, Ferguson DM, Spellmeyer DC, Fox T, Caldwell JW, Kollman PA. A Second Generation Force Field for the Simulation of Proteins, Nucleic Acids, and Organic Molecules. *J. Am. Chem. Soc*. 1995;117:5179–5197.
24. Kollman PA. Free energy calculations: Applications to chemical and biochemical phenomena. *Chem. Rev*. 1993;93:2395–2417.
25. Aqvist J, Luzhkov VB, Brandsdal BO. Ligand binding affinities from MD simulations. *Acc Chem Res*. 2002;35(6):358–365. doi: 10.1021/ar010014p.
26. Semenov VA, Krivdin LB. Combined computational NMR and molecular docking scrutiny of potential natural SARS-CoV-2 Mpro inhibitors. *J Phys Chem B*. 2022;126(11):2173–87.
27. Wu Z, Xu J, Ruan J, Chen J, Li X, Yu Y, et al. Probing the mechanism of interaction between capsaicin and myofibrillar proteins through multispectral, molecular docking, and molecular dynamics simulation methods. *Food Chem X*. 2023;18:100734.
28. Shi J, Zhao LX, Wang JY, Ye T, Wang M, Gao S, et al. The novel 4-hydroxyphenylpyruvate dioxygenase inhibitors in vivo and in silico approach: 3D-QSAR analysis, molecular docking, bioassay, and molecular dynamics. *Arab J Chem*. 2022;15(7):103919.
29. Chigurupati S, Al-Murikhy A, Almahmoud SA, Almoshari Y, Ahmed AS, Vijayabalan S, et al. Molecular docking of phenolic compounds and screening of antioxidant and antidiabetic potential of *Moringa oleifera* ethanolic leaves extract from Qassim region, Saudi Arabia. *Saudi J Biol Sci*. 2022;29(2):854–9.
30. Rizk HF, El-Borai MA, Ragab A, Ibrahim SA, Sadek ME. A novel of azo-thiazole moiety alternative for benzidine-based pigments: Design, synthesis, characterization, biological evaluation, and molecular docking study. *Polycyclic Aromat Comp*. 2023;43(1):500–22.
31. Mohanty M, Mohanty PS. Molecular docking in organic, inorganic, and hybrid systems: A tutorial review. *Monatsh Chem*. 2023;154(7):683–707.
32. Jin W, Barzilay R, Jaakkola T. Antibody-antigen docking and design via hierarchical structure refinement. *International Conference on Machine Learning* 2022 Jun 28 (pp. 10217–10227). PMLR.
33. Kwon S, Seok C. CSAAlign and CSAAlign-Dock: Structure alignment of ligands considering full flexibility and application to protein-ligand docking. *Comput Struct Biotechnol J*. 2023;21(7873):1–0.
34. Jin Z, Wei Z. Molecular simulation for food protein-ligand interactions: A comprehensive review on principles, current applications, and emerging trends. *Compr Rev Food Sci Food Saf*. 2024;23(1):1–29.
35. Carlson HA, Jorgensen WL. An extended linear response method for determining free energies of hydration. *J Phys Chem*. 1995;99:10667–10673.
36. Shoichet BK, Stroud RM, Santi DV, Kuntz ID, Perry KM. Structure-based discovery of inhibitors of thymidylate synthase. *Science*. 1993;259(5100):1445–1450. doi: 10.1126/science.8451640.
37. Michel J, Verdonk ML, Essex JW. Protein-ligand binding affinity predictions by implicit solvent simulations: a tool for lead optimization? *J Med Chem*. 2006;49(25):7427–7439. doi: 10.1021/jm061021s.
38. Briggs JM, Marrone TJ, McCammon JA. *Computational Science New Horizons and Relevance to Pharmaceutical Design*. Trends Cardiovasc. Med. 1996;6:198–206. doi: 10.1016/S1050-1738(96)00068-0.
39. Bohm HJ. Prediction of binding constants of protein ligands: a fast method for the prioritization of hits obtained from de novo design or 3D database search programs. *J Comput Aided Mol Des*. 1998;12(4):309–323. doi: 10.1023/a:1007999920146.
40. Mijit A, Wang X, Li Y, Xu H, Chen Y, Xue W. Mapping synthetic binding proteins epitopes on diverse protein targets by protein structure prediction and protein-protein docking. *Comput Biol Med*. 2023;163:107183.
41. Boyles F, Deane CM, Morris GM. Learning from the ligand: Using ligand-based features to improve binding affinity prediction. *Bioinformatics*. 2020;36(3):758–64.
42. Cleves AE, Jain AN. Structure-and ligand-based virtual screening on DUD-E+: Performance dependence on approximations to the binding pocket. *J Chem Inf Model*. 2020;60(9):4296–310.
43. Thomas M, Smith RT, O'Boyle NM, de Graaf C, Bender A. Comparison of structure-and ligand-based scoring functions for deep generative models: A GPCR case study. *J Cheminf*. 2021;13(1):39.
44. Azevedo L, Serafim MS, Maltarollo VG, Grabrucker AM, Granato D. Atherosclerosis fate in the era of tailored functional foods: Evidence-based guidelines elicited from structure-and ligand-based approaches. *Trends Food Sci Technol*. 2022;128(S13):75–89.
45. Krupa P, Karczyńska AS, Mozolewska MA, Liwo A, Czaplewski C. UNRES-Dockprotein-protein and peptide-protein docking by coarse-grained replica-exchange MD simulations. *Bioinformatics*. 2021;37(11):1613–5.
46. Lensink MF, Nadzirin N, Velankar S, Wodak SJ. Modeling protein-protein, protein-peptide, and protein- oligosaccharide complexes: CAPRI 7th edition. *Proteins*. 2020;88(8):916–38.
47. Zacharias M. Computational protein-protein docking. *Protein interactions: The molecular basis of interactomics*. 2022:53–76.
48. Soofi A, Taghizadeh M, Tabatabaei SM, Rezaei Tavirani M, Shakib H, Namaki S, et al. Centrality analysis of protein-protein interaction networks and molecular docking prioritize potential drug targets in type 1 diabetes. *Iran J Pharm Res*. 2020;19(4):121–34.

49. Gehlhaar DK, Verkhivker GM, Rejto PA, Sherman CJ, Fogel DB, Fogel LJ, Freer ST. Molecular recognition of the inhibitor AG-1343 by HIV-1 protease: conformationally flexible docking by evolutionary programming. *Chem Biol.* 1995;2(5):317–324. doi: 10.1016/1074-5521(95)90050-0.
50. Verkhivker GM, Bouzida D, Gehlhaar DK, Rejto PA, Arthurs S, Colson AB, Freer ST, Larson V, Luty BA, Marrone T, Rose PW. Deciphering common failures in molecular docking of ligand-protein complexes. *J Comput Aided Mol Des.* 2000;14(8):731–751. doi: 10.1023/a:1008158231558.
51. Jain AN. Scoring noncovalent protein-ligand interactions: a continuous differentiable function tuned to compute binding affinities. *J Comput Aided Mol Des.* 1996;10(5):427–440. doi: 10.1007/BF00124474.
52. Head RD, Smythe ML, Oprea TI, Waller CL, Green SM, Marshall GR. VALIDATE: A New Method for the Receptor-Based Prediction of Binding Affinities of Novel Ligands. *J. Am. Chem. Soc.* 1996;118:3959–3969.
53. Gehlhaar DK, Moerder KE, Zichi D, Sherman CJ, Ogden RC, Freer ST. De novo design of enzyme inhibitors by Monte Carlo ligand generation. *J Med Chem.* 1995;38(3):466–472. doi: 10.1021/jm00003a010.
54. Eldridge MD, Murray CW, Auton TR, Paolini GV, Mee RP. Empirical scoring functions: I. The development of a fast empirical scoring function to estimate the binding affinity of ligands in receptor complexes. *J Comput Aided Mol Des.* 1997;11(5):425–445. doi: 10.1023/a:1007996124545.
55. Muegge I, Martin YC. A general and fast scoring function for protein-ligand interactions: a simplified potential approach. *J Med Chem.* 1999;42(5):791–804. doi: 10.1021/jm980536j.
56. Andreani J, Quignot C, Guerois R. Structural prediction of protein interactions and docking using conservation and coevolution. *Wiley Interdiscip Rev Comput Mol Sci.* 2020;10(6):e1470.
57. Xiong G, Shen C, Yang Z, Jiang D, Liu S, Lu A, et al. Featurization strategies for protein-ligand interactions and their applications in scoring function development. *Wiley Interdiscip Rev Comput Mol Sci.* 2022;12(2):e1567.
58. Shree P, Srivastava S, Chaube R, Tripathi YB. Protein-Protein docking interaction of Nephlin protein with the expression of MMP-9: An anti-inflammatory agent. *Res J Biotechnol.* 2022;17(6):67-72.
59. Perez-Sanchez H, Kumar DT, Doss CG, Rodríguez-Schmidt R, Cerón-Carrasco JP, Peña-García J, et al. Prediction and characterization of influenza virus polymerase inhibitors through blind docking and ligand- based virtual screening. *J Mol Liq.* 2021;321:114784.
60. Che X, Chai S, Zhang Z, Zhang L. Prediction of ligand binding sites using improved blind docking method with a machine learning-based scoring function. *Chem Eng Sci.* 2022;261:117962.
61. Mazzini S, Musso L, Dallavalle S, Artali R. Putative SARS-CoV-2 Mpro inhibitors from an in-house library of natural and nature-inspired products: A virtual screening and molecular docking study. *Molecules.* 2020;25(16):3745.
62. Kawsar SM, Hosen MA, Chowdhury TS, Rana KM, Fujii Y, Ozeki Y. Thermochemical, PASS, molecular docking, drug-likeness and in silico ADMET prediction of cytidine derivatives against HIV-1 reverse transcriptase. *Rev Chim.* 2021;72(3):159-78.
63. Mitchell JBO, Laskowski RA, Alex A, Thornton JM. Bleep-potential of mean force describing protein-ligand interactions: I. generating potential. *J. Comput. Chem.* 1999;20(11):1165–1176.
64. Ishchenko AV, Shakhnovich EI. Small Molecule Growth 2001 (SMoG2001): an improved knowledge-based scoring function for protein-ligand interactions. *J Med Chem.* 2002;45(13):2770–2780. doi: 10.1021/jm0105833.
65. Feher M, Deretey E, Roy S. BHB: a simple knowledge-based scoring function to improve the efficiency of database screening. *J Chem Inf Comput Sci.* 2003;43(4):1316–1327. doi: 10.1021/ci030006i.